

MARINE EMERGENCY REPAIR KITS

DAMAGE CONTROL



Description

Required damage control locker inventory for the U.S. Coast Guard and the U.S. Navy. Syntho-Glass® provides a fast, reliable, and durable solution in emergencies. Each kit contains enough material to repair several leaks in hoses, onboard piping, and hydraulic lines, or make temporary repairs to mechanical equipment. In addition, Syntho-Plug will repair hull damage to ensure a safe trip home. Works with fiberglass, steel, or aluminum boats, in freshwater, brackish water, or saltwater, and can be applied above or below the water line.

Medium Damage Control Kit for Vessels < 29'	Large Damage Control Kit for Vessels > 30'	XL Damage Control Kit for Vessels > 50'
Item #: MarineEmergMed	Item #: MarineEmergLg	Item #: MarineEmergXL
2.5" Syntho-Plug	(2) 2.5" Syntho-Plug	(4) 2.5" Syntho-Plug
Repair Kit for up to 2" OD Pressurized	Repair Kit for up to 2" OD Pressurized	Repair Kit for up to 2" OD Pressurized
Repair Kit for up to 2" OD Non-pressurized	Repair Kit for up to 4" OD Pressurized	Repair Kit for up to 4" OD Pressurized
Steel Reinforced, Two-Part Putty Stick 7" (4.25 oz. ea.)	Repair Kit for up to 2" OD Non-pressurized	Repair Kit for up to 6" OD Pressurized
Watertight Safety Container	Repair Kit for up to 4" OD Non-pressurized	Repair Kit for up to 2" OD Non-pressurized
	(2) Steel Reinforced, Two-Part Putty Stick 7" (4.25 oz. ea.)	Repair Kit for up to 4" OD Non-pressurized
	Watertight Safety Container	Repair Kit for up to 6" OD Non-pressurized
		(3) Steel Reinforced, Two-Part Putty Stick 7" (4.25 oz. ea.)
		Watertight Safety Container

*Custom kits available upon request. See back for kit descriptions.

Typical Applications

- Water, fuel, or bilge pump leaks
- Fuel or water tank leaks
- Hull breaches or damage

Benefits

- Ready to use
- Heat resistant
- Effective, time-saving
- No mixing and no mess
- Sets rock hard
- Approved for potable water

“Saved an entire Alaskan King Crab fishing season.”

- Jim Stone, Captain of the Retriever Discovery Channel's *Deadliest Catch*




This kit will give you the opportunity to repair a leak temporarily or permanently to ensure your safe arrival home.




SYNTHO-GLASS Description

Syntho-Glass is the originally, patented fiberglass pre-impregnated composite that is activated by saltwater or freshwater. Packaged in a hermetically sealed foil pouch, it is ready to use and does not require any measuring or mixing. This system, when used with the appropriate primary patch, enables you to repair and reinforce virtually any diameter pipe in minutes. Syntho-Glass not only restores a pipe to its original PSI rating, but actually can make the repair area stronger than the original pipe, reducing downtime, saving in parts and labor. With an initial setting time of only 30 minutes (75°F), Syntho-Glass is excellent on copper, steel, SS, PVC, FRP, clay, concrete, rubber, and more. It is safe to use, nontoxic, noncombustible, and odorless. Syntho-Glass is a versatile solution for when quick-action repair can be critical.

SYNTHO-GLASS^{UP} Description

Syntho-Glass^{UP} Repair System was specifically designed for under pressure pipe repair. By combining the original Syntho-Glass product with the extremely chemically resistant Syntho-SteelTM and unique Pressure Sealing Rubber Tape, this system offers the geometric flexibility to repair joints, tees, couplings, and pinholes. This complete system simplifies the application process and is prepackaged to accommodate pipes up to 10 inches in diameter. Larger repair applications can be engineered to meet your requirements. 


SYNTHO-GLASS^{NP} Description

Syntho-Glass^{NP} Repair System was specifically designed for depressurized pipe repair. By combining the original Syntho-Glass product with the extremely chemically resistant Syntho-Steel, this system offers the geometric flexibility to repair joints, tees, couplings, and pinholes. This complete system simplifies the application process and is prepackaged to accommodate pipes up to 10 inches in diameter. Larger repair applications can be engineered to meet your requirements. 

SYNTHO-PLUG Description

Syntho-PlugTM is a polyurethane impregnated, water-activated foam plug used to temporarily repair hull damage ensuring a safe trip home. It is initially pliable to insert into void and quickly hardens to seal the void. Works with fiberglass, steel, or aluminum boats, in freshwater, brackish water, or saltwater, and can be applied above or below the water line.

SYNTHO-STEEL Description

Syntho-SteelTM is a two-part, steel reinforced epoxy putty. It cures in minutes and can repair most anything made of metal, masonry, wood, ceramic, glass, and plastic. Syntho-Steel contains no solvents and is nontoxic and easily prepared for application. Unlike liquid epoxies, Syntho-Steel will not drip or sag, and will set on wet surfaces. 

Item #	Description
UPM520	Repair Kit for up to 1" OD Pressurized
UPM930	Repair Kit for up to 2" OD Pressurized
UPM415	Repair Kit for up to 4" OD Pressurized
UPM430	Repair Kit for up to 6" OD Pressurized
UPM650	Repair Kit for up to 10" OD Pressurized
NPM520	Repair Kit for up to 1" OD Non-pressurized
NPM930	Repair Kit for up to 2" OD Non-pressurized
NPM415	Repair Kit for up to 4" OD Non-pressurized
NPM430	Repair Kit for up to 6" OD Non-pressurized
NPM650	Repair Kit for up to 10" OD Non-pressurized
SS07	Steel Reinforced, Two-Part Putty Stick 7" (4.25 oz. ea.)

UP Kit Contents

- Step-by-Step Instructions
- Sanding Cloth
- Solvent Cleaning Wipe
- Protective Gloves
- Butyl Strip
- Syntho-Steel Putty
- Pressure Sealing Rubber Tape
- Syntho-Glass
- Compression Film

NP Kit Contents

- Step-by-Step Instructions
- Sanding Cloth
- Solvent Cleaning Wipe
- Protective Gloves
- Butyl Strip
- Syntho-Steel Putty
- Syntho-Glass
- Compression Film

©Neptune Research Inc. (NRI) NRI[®], Syntho-Glass[®], Syntho-Glass^{UP}, Syntho-Glass^{NP} are registered trademarks of NRI while Syntho-SteelTM and Syntho-PlugTM are trademarks of NRI. NRI utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact your local NRI distributor or office for the most current product specifications. NRI warrants the quality of this product when used according to directions. Syntho-Glass, Syntho-Glass UP, and Syntho-Glass NP are NOT an approved coating system. Failing to coat per standard procedures can lead to atmospheric corrosion damage. Apply protective coatings per company standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement. SGMarine DS 0112

