

SYNTHO-PLUG™

THRU HULL & SPILL CONTAINMENT REPAIR PLUG



Description

Syntho-Plug™ is a polyurethane impregnated, water-activated foam plug used to temporarily repair hull damage ensuring a safe trip home or to mitigate spill containment. It is initially pliable to insert into void and quickly hardens to fill the void, reducing water intake, or output, from 280 GPM to less than 1 GPM. Works with fiberglass, steel, wood or aluminum, in fresh, brackish, or saltwater, and can be applied above or below the water line.



Item #	Description
SP635	Syntho-Plug 3.25" OD X 6" for up to 2.5" OD Repair

Typical Applications

- Thru hull damage
- Spill containment

Benefits

- Ready to use
- Simple application
- Effective, time saving
- No mixing, no mess
- Sets rock hard in minutes

Kit Contents

- Step-by-Step Instructions
- Protective gloves
- Syntho-Plug

Physical Properties

Color: Foam - Yellow, Urethane - White
 Cure Time: 1 Minute at 75°F (24°C)
 Resin Type: Pre-impregnated
 Application Temperature:
 32° to 160°F (0° to 71°C)
 Shelf Life: 12 Months with recommended storage conditions

©Neptune Research Inc. (NRI) NRI® is a registered trademark, while Syntho-Plug™ is a trademark of NRI. NRI utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact your local NRI distributor or office for the most current product specifications. NRI warrants the quality of this product when used according to directions. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement. SP DS 0112

